



Airborne Observation Opportunities

NASA/Science Mission Directorate Airborne Science Program



Bruce Tagg, SMD/Airborne Science Program Director David Pierce, SMD/Senior Program Executive Suborbital Research

Website: http://airbornescience.nasa.gov





SMD Suborbital Research Program

The SMD Suborbital Research Program powers scientific discovery, technological and educational investigations on suborbital vehicles through:

- Conducting cutting edge Earth and Space science
- Calibration/validation of satellite measurements
- Developing technologies (science detectors and platforms) to improve Earth and space observation capabilities
- Promoting STEM through conducting exciting hands-on student training missions

Suborbital Research Program is well-suited to:

- · Quickly address new science phenomena
- Carry out significant science investigations at a fraction of the cost of a flight project
- Effective springboard for future spacecraft science missions
- Train next generation of researchers







Airborne Science Program



The NASA Airborne Science Program (ASP) within the Earth Science Division, provides NASA and commercial aircraft that benefit the earth science community. These manned and unmanned aircraft carry sensors that provide data to support and augment NASA spaceborne missions. The primary objectives of this program are:

- Conduct in-situ atmospheric measurements with varying resolutions
- Collect high-resolution imagery for process studies and sub-pixel resolution for spaceborne calibration
- Implement observational strategies for conducting earth science missions
- Demonstrate and exploit the capabilities of unmanned aerial systems (UAS) and autonomous aircraft for science investigations
- Test new sensor technologies in space-like environments
- Calibrate/validate space-based measurements and retrieval algorithms
- NASA's Airborne Science Program (ASP) conducts frequent global aircraft investigations in support of the NASA Earth Science community.
- Altitudes: up to 21 km; Durations: up to 30 hr
- Conduct an average of 17 missions/deployed field campaigns per year, utilizing more than 15 NASA aircraft and UASs.







Center Aircraft Offices

- SMD Airborne Science Program is implemented through NASA Aircraft Offices: ARC, AFRC, GSFC/WFF, GRC, JSC, and LaRC
- Responsible for operation, maintenance, engineering, airworthiness, and mission support of assigned NASA and non-NASA aircraft/UAS as well as the planning and execution of Airborne Science missions for SMD.
- Provide logistical airlift needs, recovery operations, and a wide array of other aircraft functions.
- These Aircraft Offices operate aircraft on behalf of SMD worldwide.
- The knowledge and expertise of our personnel and aircrews, along with specific aircraft capabilities, allows SMD to support any type of mission requested by customers from commercial/military airfields to austere locations.
- The SMD Airborne Science Program is committed to safe, reliable, cost effective aircraft operations to support the NASA science community.



P-3 Orion



C-130 Hercules




DC-8




Center Aircraft Offices Aircraft Mission Support



- Mission Management
 - Logistics
 - Mission planning (cost, schedule, etc.)
 - Field support
 - Ground and flight safety support
- Engineering
 - Installation design and analysis
 - Upload and download support
- Airworthiness Oversight
- Maintenance Support
 - Assist with installation and removal of equipment from the aircraft








NASA Earth Science Research Capable Aircraft







NASA Airborne Science Program Core Aircraft







NASA Airborne Science Program Other NASA Aircraft








2005-2014 Airborne Campaigns










Deployments Over the Years









Supported Aircraft	Platform Name	Center	Duration (hours)	Useful Payload (lbs)	GTOW (lbs.)	Max Altitude (ft)	Air Speed (knots)	Range (Nmi)
	DC-8	NASA - DFRC, UND	12.00	30,000	340,000	41,000 ft.	450	5,400
	ER-2	NASA-DFRC	12.00	2,900	40,000	70,000 ft	410	5,000
oddne	G-III (C-20A) - Dryden	NASA-DFRC	7.00	2,500	69,700	45,000	460	3,400
0	G-III - JSC	NASA-JSC	7.00	2,610	69,700	45,000	460	3,650
ASS	Global Hawk	NASA - DFRC	30.00	1,900	25,600	65,000 ft	345	11,000
	P-3 Orion	NASA-WFF	14.00	14,700	135,000	32,000 MSL	400	3,800
	Platform Name	Center	Duration (hours)	Useful Payload (lbs)	GTOW (lbs.)	Max Altitude (ft)	Air Speed (knots)	Range (Nmi)
	B-200 (UC-12B) - LARC	NASA-LARC	6.20	4,100	13,500	31000 ft	260	1,250
	B-200 - DFRC	NASA-DFRC	6.00	1,850	12,500	30,000	272	1,490
	B-200 - LARC	NASA-LARC	6.20	4,100	13,500	35000 ft	260	1,250
	B-200 King Air - WFF	NASA-WFF	6.00	1,800	12,500	32,000 feet	275	1,800
	C-130 Hercules	NASA-WFF	10.00	36,500	155,000	33,000 ft.	290	1,050
	C-23 Sherpa	NASA-WFF	6.00	7,000	27,100	20,000 ft	190	1,000
	C-9B	NASA-JSC			110,000	37000	490	2,000
	Cessna 206H	NASA-LARC	5.70	1,175	3,600	15700 ft	150	700
	Dragon Eye	NASA Ames Research Center	1.00	1	6	500+	34	3
	HU-25C Falcon	NASA-LARC		3,000	32,000	42000	430	1,900
	Ikhana	NASA-DFRC	24.00	2,000	10,000	> 40,000 ft.	171	3,500
	Learjet 25	NASA- GRC	3.00	3,200	1,500	45,000 ft.	350	1,200
	S-3B	NASA-GRC	6.00	12,000	52,500	40000 ft	450	2,300
aff	SIERRA	NASA-ARC	10.00	100	400	12,000 ft.	60	600
Other NASA Aircraft	T-34C	NASA-GRC	3.00	500	4,400	25000 ft.	75	700
	Twin Otter - GRC	NASA-GRC	3.00	3,600	11,000	25,000	140	450
	UH-1 Huey	NASAWFF	2.00	3,880	9,040	12000	108	275
	WB-57	NASA-JSC	6.50	8,800	72,000	60,000 ft and above (payload dependent)	410	2,500
	XSCAV	NASA-ARC	4.00	50	130		30	





P-3 Orion Aircraft – N426NA

P-3 Orion Description:

Four T56-A-14 turboprop engines Extensively modified for NASA science use:

- Two bomb bay ports, Nose radome port, Tailcone port
- One 16" dia. zenith port
- Three nadir ports
- Wing mounts
- Four P-3 bubble and three DC-8 passenger windows

115V 60Hz and 400Hz power along with 28VDC

Lavatory and galley on board

Max altitude: 30,000 feet; Max airspeed: 400 KTAS

Max endurance time: 14 hours (~3,800 miles)

Minimum runway length: 7,000 feet

Payload capacity: ~14,700 lbs











Airborne Data System


- ◆ REVEAL/NASDAT system operated by UND (same system as on DC-8)
- ◆ Recording of aircraft parameters and facility instrumentation data via ARINC 429, MIL-STD-1553, analog channels and network inputs
- ♦ Recording of experimenter data via analog channels, RS-232, network inputs and video feeds
- Redundant, reliable data storage
- Retransmission of data within the aircraft via RS-232 and Ethernet to onboard instrumentation
- ◆ Transmission of data to and from the ground and other aircraft in real time via satellite communications
- High-performance time services
- Real-time text-based chat
- Web-based situations awareness displays





P-3 – Typical Mission Layout









Typical Aircraft Modifications



7/1/2015



DC-8



- The DC-8 Flying Laboratory is a uniquely capable asset supporting NASA Earth science missions.
- Altitude: 41,000 ftPayload: 30,000 lbsRange: 5,400 nmi
- 1 Zenith View Port 16"x18"
- 13 Modified Window Frames 16"x18"
- 4 Zenith 62⁰ View Ports 16"x21"
- 2 Nadir View Ports 37"x30"
- 3 Nadir View Ports 16"x21"
- 1 Nadir Camera Port
- 9 Optical Window Shutters
- Wing Tip Pylons/Pods
- Dropsonde Port/Launcher Tube
- Wing Root Radome Panels
- Removable Weather Radar Antenna
- 1 INMARSAT Antenna
- MMS 102 TAT Sensor Installation Locations
- 12 Channel IRIDIUM & GPS Antenna Farm
- Standard 19" rack mounting provisions in cabin and cargo spaces






ER-2




- 3 Zenith ports are currently available in the Q-bay
- 2 of 4 Aft tail cones have zenith openings* that can be customized
- 1 of 4 Forebody wing pods have openings* that can be customized
 *Openings are not considered "ports" since
 they are open to the environment (no glass).




This graphic displays the current configuration. Custom ports can be configured in many locations on the aircraft – design and fabrication cost/schedule apply



WB-57: Capable



PERFORMANCE				
Aircraft ceiling	60,000+ feet			
Endurance	6.5 hours			
Range	2,500 miles			
Max. payload	8,800 pounds			
Airspeed @ 60kft	410 knots (Max: Mach 0.8)			
Aircrew	2			
Wingspan	123 feet			





WB-57: Adaptable



TAIL ORED SENSOR SOLUTIONS

- Unique access to cutting-edge technologies across NASA / DoD / national agencies not currently available through existing service or industry platforms.
- No "standard payload" constraints.
- Sensor package(s) compiled to meet each mission's requirements.
- Platform capable of integrating, testing and employing customer sensors.
- Multiple air-to-ground communication options: Voice, BLOS & LOS datalinks.
- Multiple payload power options: 110V 400Hz, 110V 60Hz, & 28VDC.







SENSOR INTEGRATION OPTIONS

- A Reconfigurable/removable, pressurized nose cone
- **B** 4 hard points 2/wing; compatible with ER-2 SPEAR Pod, Super Pod and BRU's;
- C 12' bomb bay (3 'or 6' Universal Pallet System); 1000lb capacity per 3' space
- 20x small sensor hatches; ten hatches per wing
- Tail cone / upper equipment bay



Global Hawk



- NASA maintains 2 Global Hawk UAS specifically targeted to support SMD science operations.
- The Global Hawk Operations Center –
 provides command and control for the AFRC
 Global Hawk aircraft (located at AFRC and
 GSFC/WFF). This center acts as a primary
 operating location for Global Hawk flight
 crews and experimenters flying experiments
 around the world or as a backup center the
 west coast



Global Hawk UAS

	24-26 hours for Typical Missions
Endurance	28.6 hours Demonstrated
Range	10,000 nmi
Service Ceiling	65,000 ft, < 50% available A/C payload power
Service Celling	62,500 ft, > 50% available A/C payload power
Airspeed (55,000+ ft)	335 KTAS
Payload	1,200 lb Demonstrated
Length	44 ft
Wingspan	116 ft



GSFC/WFF Global Hawk Operations Center





C-130 Hercules – N439NA

C-130 Hercules Description:

- Former USAF cargo aircraft
- ◆ Four T56-A-15 turboprop engines
- Aircraft features:
 - Aft cargo ramp (opens outward and inward)
 - Elongated nose with nadir port
 - 55" dia. nadir port
 - Large side removable fuselage plug
 - 120V 60Hz and 400 Hz experimenter power available along with 28VDC
 - Extra air conditioning for high heat loads
- ◆ Max altitude: 33,000 feet
- Max airspeed: 320 knots
- Max endurance time: 8-10 hours
- ◆ Max. range: 3,200 nmi.
- Minimum runway length: 1,400 to 3,500 feet
- ◆ Payload capacity: 45,000 lbs





Payload in C-130





B-200 King Air – N8NA

• B-200 Description:

- Passenger style tubroprop business aircraft
- Wing span: 54 feet 6 inches
- Length: 43 feet 9 inches
- Height: 15 feet
- ◆ Two PT6A-42 turboprop engines
- Ports available for NASA science use:
 - 8 non-removable windows
 - GPS/Iridium experimenter antennas installed
- ◆ 28VDC experimenter power
- Max altitude: 32,000 feet
- Max airspeed: 275 KTAS
- ♦ Max endurance time: 6 hours (~1,800 miles)
- ◆ Payload capacity: ~1,800 lbs
- Max crew: 10 persons
- Due FAA standard certificate to conduct passenger flights this aircraft can not be modified for science except for reconfiguring the cabin to utilizing the existing window.



B-200 King Air





Airborne Support for Sounding Rockets Missions

- November 2014 Norway/Andoya Space Center Campaign
- The C-REX mission launched on a fourstage Talos-Terrier-Brant-Nihka (Black Brant XII) to a projected altitude of 328 miles carrying the Cusp-Region Experiment (C-REX) payload.
- 24 sub-payloads were ejected from the rocket as it flew to nearly 302 miles altitude.
- Ground–based cameras and those on a <u>NASA King Air B-200 aircraft</u> tracked the tracers.
- The science team gathered data of the vapor cloud releases, using ground cameras and cameras flown aboard the NASA B200 aircraft.











C-23 Sherpa Aircraft – N430NA

C-23 Sherpa Description:

- Former Army National Guard logistics aircraft
- Wing span: 74 feet 10 inches
- Length: 58 feet 1 inches
- Height: 16 feet 5 inches
- Two PT6A-65AR turboprop engines
- Aircraft features
 - Aft cargo ramp (opens outward and inward)
 - Nose cargo opening (holds 400lbs)
 - 22 removable passenger windows
 - Large port cargo door
 - 28VDC converted to 115VAC
 - Unpressurized, passenger O2 available
 - Lavatory available
- ♦ Max altitude: 20,000 feet
- Max airspeed: 196 KIAS
- ♦ Max endurance time: 6.5 hours (~1,800 miles) w/aux tanks
- Minimum runway length: 3,000 feet
- ◆ Payload capacity: ~7,000 lbs
- Max crew: 10 persons







Science Operations Flight Request System (SOFRS)





Steven Todorov, SOFRS Manager Earth Science Project Office steven.m.todorov@nasa.gov (650) 996-9335

Sommer Beddingfield, SOFRS Curator Earth Science Project Office sommer.l.beddingfield@nasa.gov (650) 604-5966

Bruce Tagg, Director
Airborne Science Program
Earth Sciences Division
bruce.a.tagg@nasa.gov


https://airbornescience.nasa.gov



Science Operations Flight Request System (SOFRS)



Science Flight Planning Communication and Reporting Tool



300+ different instruments

50+ different aircraft

4,600+ annual science flight hours


27 different reports



Science Operations Flight Request System (SOFRS)



ASP Flight Request (FR)Approval Process





Program

Platforms

Instrumentation

Mission Tools

Flight Request

> Log in to Airborne Science

Create New Account

Search

▼ Program

Current Activities

News

Student Airborne Research

Program

Documents

ASP Blog

Points of Contact

Research Opportunities

Related Links

Videos

- Platforms
- Instrumentation
- Mission Tools

Flight Request

Documents

Airborne Science Program Spring 2015 newsletter

ASP FY15 Call Letter Rev 2

Airborne Science Program 2014
Annual Report

More Documents

NASA Airborne Science Program

News



NASA ER-2 Completes Suomi-NPP Arctic Validation Mission

NASA's high-altitude ER-2 aircraft completed a series of validation flights last month in support of the Earth-observing NASA/NOAA Suomi National Po...

Read More:

01 02 03 **04** 05 06 07 II

View News Archive

About the Airborne Science Program

The Airborne Science Program within the Earth Science Division is responsible for providing aircraft systems that further science and advance the use of satellite data. The primary objectives of this program are to:

Satellite Calibration and Validation

Current Activities

Operation IceBridge



Visit Mission Website

Airborne Surface Water and Ocean Topography (AirSW...

G-III UAVSAR

More Current Activities

Asset Tracker

8-200 - LARC 8-200 - WFF Catalog



Program

Platforms

Instrumentation

Mission Tools

Flight Request

> Log in to Airborne Science | > Create New Account

Search

▼ Program

Current Activities

News

Student Airborne Research

Program

Documents

ASP Blog

Points of Contact **Research Opportunities**

Related Links

Videos

- Platforms
- Instrumentation
- **Mission Tools**

Flight Request

Documents

Airborne Science Program Spring 2015 newsletter

ASP FY15 Call Letter Rev 2

Airborne Science Program 2014 **Annual Report**

More Documents

NASA Airborne

Science Program News



NASA Study Shows Antarctica's Larsen B Ice Shelf Nearing Its...

A new NASA study finds the last remaining section of Antarctica's Larsen B Ice Shelf, which partially collapsed in 2002, is quickly weakening and like... Read More:

01 02 03 04 05 06 07 II

View News Archive

About the Airborne Science Program

The Airborne Science Program within the Earth Science Division is responsible for providing aircraft systems that further science and advance the use of satellite data. The primary objectives of this program are to:

Satellite Calibration and Validation

Current Activities

Operation IceBridge

Airborne Surface Water and Ocean Topography (AirSW...



Visit Mission Website

G-III UAVSAR

More Current Activities

Asset Tracker



Program

Platforms

Instrumentation

Mission Tools

Flight Request

> My accou

Log out

Search

SOFRS

New Flight Request

Flight Requests

User Control Panel

How To Submit a Flight Request

- ▶ Program
- Platforms
- Instrumentation
- Mission Tools

Flight Request

ESPO Archive

- Browse Archive Upload Files
- Help

NAS Airborne Saence Program



Home > Science Operations Flight Request System (SOFRS)

Science Operations Flight Request System (SOFRS)

Accessing NASA Airborne Science Platforms and Instruments

The Airborne Science Program (ASP) maintains aircraft and sensor assets to support the Science Mission Directorate (SMD). The Science Operations Flight Request System (SOFRS) manages and tracks the allocation of the ASP aircraft and facility sensors. The aircraft (platform) as well as facility sensor (instrumentation) information is accessible through the Airborne Science Program website.

Requests for scheduling these assets shall be submitted through the system was designed to allow researchers to have access to unique NASA aircraft, as well as some common arrangements.

The only way to schedule the use of NASA SMD platand instrument assets is to submit a Flight Request through SOFRS.

Otep by step instructions for submitting a Flight Request are at this link: HOW TO SUBMIT A FLIGHT REQUEST

User Fees

The assets of the program are available on a fee-for-service basis, although, because the SMD maintains a base capability, only the marginal cost of the actual missions are borne by experiments given NASA HQ science concurrence. User fees are based on the flight hour cost (e.g. pilots, in-flight engineer, fuel, etc..), mission-specific costs (engineering and deployment costs) and any ancillary support costs (satellite communication requirements, facility instrument data and operations costs).



Airborne Science Program Contact





Bruce Tagg, Director
Airborne Science Program
Earth Sciences Division
bruce.a.tagg@nasa.gov

https://airbornescience.nasa.gov